

POWERED BY



T-10-NM

Termination Load, 0–3000 MHz

General Specifications

| | |
|-------------|------------------|
| Brand | Andrew® |
| Device Type | Termination Load |
| Interface | N Male |
| Color | Black |

Electrical Specifications

| | |
|--------------------------|--------------|
| Operating Frequency Band | 0 – 3000 MHz |
| Average Power, maximum | 10 W |
| Impedance | 50 ohm |
| Return Loss, minimum | 23.0 dB |
| VSWR | 1.15:1 |

Mechanical Specifications

| | |
|-----------------------|----------|
| Inner Contact Plating | Silver |
| Outer Contact Plating | Trimetal |

Environmental Specifications

| | |
|--------------------------------|--------------------------------------|
| Application | Indoor/Outdoor |
| Ingress Protection Test Method | IEC 60529:2001, IP65 |
| Operating Temperature | -35 °C to +50 °C (-31 °F to +122 °F) |
| Relative Humidity | Up to 100% |

Dimensions

| | |
|-------------------|--------------------|
| Diameter, maximum | 35.00 mm 1.38 in |
| Length | 53.50 mm 2.11 in |
| Net Weight | 110.00 g 0.24 lb |

Packed Dimensions

| | |
|-----------------|--------------------|
| Height | 68.0 mm 2.7 in |
| Length | 58.0 mm 2.3 in |
| Width | 53.0 mm 2.1 in |
| Shipping Weight | 135.00 g 0.30 lb |

T-10-NM

Volume

209.0 mm³

POWERED BY



Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

ISO 9001:2008

Classification

Above Maximum Concentration Value (MCV)

Designed, manufactured and/or distributed under this quality management system

